




AKTS3206TN



Ventilated refrigerated counter with 3 doors and raised back, depth 600 mm



- Stainless steel external and internal structure
- 10 cm raised back
- Ventilated refrigeration with incorporated refrigeration unit
- Ducted ventilation
- Digital control unit
- Extractable refrigeration monoblock unit
- Anticorrosion treated evaporator
- Door frame with thermal break
- Automatic defrost
- Automatic condensation evaporation
- 70 mm insulation thickness
- Easily removable magnetic gaskets
- Internal rounded edges
- Service compartment with key lock
- External bottom and back panels in galvanized steel
- Adjustable stainless steel feet
- Equipped with 3 330x430 mm shelves
- 4 casters kit (2 of which with brake) model RBA7 available on request

TECHNICAL FEATURES

| | |
|------------------------|------------------|
| MODEL | AKTS3206TN |
| ENERGY CLASS | C (2015/1094/UE) |
| CLIMATE CLASS | 4 |
| POWER WATT | 270 |
| POWER SUPPLY | 230/1N/50 |
| TEMPERATURE °C | 0 ÷ +8 |
| REFRIGERANT | R290 |
| MAX. TEMP. / HUMIDITY | +40 °C / 60% HR |
| DIMENSIONS MM | 1800x600x950h |
| INTERNAL DIMENSIONS MM | 1280x450x575h |
| CAPACITY L | 331 |
| SHELVES NO. AND TYPE | 3 x 330x430 mm |
| NET WEIGHT KG | 83 |
| GROSS WEIGHT KG | 100 |
| PACKING DIMENSIONS CM | 184x62x98h |