

= RISOPL / NET


AKD600RG














- White painted steel external structure
- · ABS internal structure
- · Cooling plate static refrigeration with fan to uniform the temperature
- · Door integrated digital control unit
- Automatic defrost
- Automatic condensation evaporation
- · Double glazed door with plastic frame
- 40 mm insulation thickness
- · Easily removable magnetic gasket
- Internal rounded edges
- Internal LED lighting with ON/OFF switch
- Door with key lock
- Equipped with 3 650x525 mm and 1 650x335 mm shelves
- Interal guides compatible with GN2/1 pans and shelves

TECHNICAL FEATURES

MODEL	AKD600RG
ENERGY CLASS	B (2019/2018/UE)
POWER WATT	130
POWER SUPPLY	230/IN/50
TEMPERATURE °C	+2 ÷ +8
REFRIGERANT	R600a
MAX. TEMP. / HUMIDITY	+33 °C / 60% HR
DIMENSIONS MM	777x710x1895h
INTERNAL DIMENSIONS MM	650x530x1620h
CAPACITY L	580
SHELVES NO. AND TYPE	3 x 650x525 mm
	1 x 650x335 mm
NET WEIGHT KG	106
GROSS WEIGHT KG	122
PACKING DIMENSIONS CM	84x76x201h